

Treillis soudés

Bouwstaalnetten

Treillis standard 5,00 m x 2,00 m

Standaardnetten 5,00 m x 2,00 m

Mailles Mazen	Fils Draden	Poids commercial Handels- gewicht	Section dans une direction Sectie in één richting	Nombre par tonne Aantal per ton
mm	mm	kg Treillis/Net	cm ² /m	N ₆
75 x 75	4 x 4	27,05	1,68	36
75 x 75	5 x 5	42,22	2,62	23
100 x 100	4 x 4 (*)	20,08	1,26	49
100 x 100	5 x 5	31,39	1,96	31
100 x 100	6 x 6	45,25	2,83	22
100 x 100	8 x 8	80,51	5,03	12
100 x 100	10 x 10	125,76	7,85	7
100 x 100	12 x 12	180,99	11,31	5
150 x 150	4 x 4 (*)	13,22	0,84	75
150 x 150	5 x 5	20,56	1,31	48
150 x 150	6 x 6	29,64	1,88	33
150 x 150	8 x 8	52,74	3,35	18
150 x 150	10 x 10	82,37	5,24	12
150 x 150	12 x 12	118,55	7,54	8
200 x 200	4 x 4 (*)	10,19	0,63	98
200 x 200	5 x 5	15,69	0,98	63
200 x 200	6 x 6	22,62	1,41	44
200 x 200	8 x 8	40,25	2,51	24
200 x 200	10 x 10	62,88	3,93	15
200 x 200	12 x 12	90,50	5,65	11

Treillis avec cotés ouverts 5,95 m x 2,5 m

Netten met stekeinden 5,95 m x 2,5 m

150 x 150	6 x 6	41,68	1,88	23
150 x 150	7 x 7	56,70	2,57	17
150 x 150	8 x 8	70,77	3,35	14
150 x 150	9 x 9	89,40	4,24	11
150 x 150	10 x 10	110,54	5,24	9
150 x 150	11 x 11	127,24	6,34	7
150 x 150	12 x 12	151,45	7,54	6

(*)= geen BENOR

(*)= non BENOR

